

HJB 110 T4 0,75KW (509111044)

GENERAL DATA



BELT DRIVE AXIAL FAN FOR HUGE AIR FLOW

MANUFACTURING FEATURES:

- Completely made of galvanized steel sheet.
- Equipped with gravity shutter.
- Stainless steel impeller (AISI 430).
- Protection grid on pulley area.
- Standard asynchronous squirrel-cage motor with IP-55 protection and class F insulation.

Manufactured with standard voltage: 230/400V 50Hz IE3

• Internal wiring box. Inspection door for motor access.

APPLICATIONS:


Designed for wall assembly, they are suitable for:

- Air renewal in buildings and industries.
- Farms and greenhouses.
- Maximum working temperature: 50°C.

UNDER REQUEST

Option 60Hz

PERFORMANCE CURVE



TECHNICAL DATA

Fan								
RPM	1450	Approx. weight	88 kg	Max. Flow	32300 m³/h			
Motor								
Power	0,75 kW	RPM	1450	I max. (230V)	3,5 A	I max. (400V)	2 A	













DIMENSIONS




Dimensions (mm)

A 1100 C 400

WIRING DIAGRAM











ACCESSORIES



SAFETY SWITCH INT 25 3P A REF: INT253PA




FREQUENCY SPEED CONTROLLER SFC 230 I 4,2A * **REF:** SFC230I004



FREQUENCY SPEED CONTROLLER SFC 400 III 2,2A * REF: SFC400III2

SPARE PARTS



	Code	Model	Qt y
1	509111044SP71	IMPELLER HJB 110	x1
2	509111044SP52	PULLEY+BEARING HJB110/120/140	x1
3	509111044SP21	BELT HJB110 B1829mm	x1
4	509111044SP31	PULLEY HJB110 B108mm	x1
5	509111044SP41	MOTOR 0,75kW T4 B3 230/400V (HJB)	x1

